




**Still & Sparkling
Pure & Simple**

Effective March 2019

2019 Catalog

Specifying Guide for the Crysalli Artisan Water Systems



Make a decision between choosing a remote chiller, countertop chiller, cabinet configuration or cold plate style model

If you selected a remote chiller unit, proceed to **Step 2** (go to page 5)

If you selected a countertop unit, proceed to **Step 4** (go to page 10)

Quick List

Step One (page 3)

Select your package between Countertop or Remote Chiller

For Remote Chiller proceed to Step 2

For Countertop proceed to Step 4

Step Two (page 5)

Select a tower and the number of taps needed

Step Three (page 8)

Select a drip/drain pan

Step Four (page 9)

Select your Crysalli Chiller Unit

For Remote Chillers go to page 9

For Countertop units go to page 10

For Low Volume units go to page 13

Step Five (page 15)

Choose an installation kit and

Add an additional trunk line if required

Step Six (page 16)

Select a water filtration system

In order to have a complete system, you must make a selection in Steps 1-6

Remote Chiller or Countertop Configuration

Custom configurations of Remote Chillers and Tower
or Countertop dispensing equipment

Featured Benefits



Countertop

- Stylish curved look with mirrored stainless exterior
- 4 model sizes for different volume needs
- Minimal countertop space use for large volume systems
- Pull Handle dispensing valve styles are great for wait staff service use
- Push Button dispensing styles are ideal for self-service use
- Single piece of equipment package just add the filter system; easy install
- Self-contained refrigeration
- Easy service accessibility
- Average dispensing temps of 34-40°
- Cold Carbonation for ideal sparkling water bubbles



Remote Chillers

- Pair with different draft tower dispensing options
- Sleek CBR draft towers in Chrome or White
- Illuminated Medallion style draft towers
- Push Button dispensing towers
- 3 model size Remote Chillers
- Can be located up to 50' away from towers
- Remotely locating chiller reduces noise and heat
- Or they can be placed in a well ventilated cabinet
- A single remote chiller can operate two towers
- Average dispensing temps of 34-40°
- Cold Carbonation for ideal sparkling water bubbles

510.732.0100

Sizing Guide

Model	Average Usage under 40° water	Usage Type	# of Seats/People
CR-1 variations and CR-UCM1	32-50 liters/8-13 gal per hour	Bottle service or craft beverage	Under 75 seats, 2-3 turns
CR-2 variations and CR-UCM2	Higher volume faster recover 64-80 liters/ 17-21 gal per hour	Bottle service, craft beverage, cafeteria, split tower systems	100 plus seats, high turn, or heavy short term peak use
CR-UCM2-2CL	Higher volume faster recover 64-80 liters/ 17-21 gal per hour	Improved still water pressure results from split tower systems, vertical risers or lower water pressure buildings	100 plus seats, high turn, or heavy short term peak use
CR-UCM2-S0096	Higher volume faster recover 64-80 liters/ 17-21 gal per hour	Long draw with a lengths farther than 45'. Vertical trunkline runs longer than 15'. Challenging trunkline runs	100 plus seats, high turn, or heavy short term peak use
CP2000 Series	Filling glasses by the oz, less than a liter per draw. Repeated use of 50, 12 oz drinks per hour ave. or periodic bottle filling	Service by the glass. Craft beverage. Coffee shops, cafes, wineries and offices	Less than 50 employees
CR-CPS Series	Ice Chilled Cold Plate. Manual fill, 40 LB Ice Storage. Melt off depends on usage. Heavy usage can require refilling every 30 min.	Self Service only. Tight spaces where Refrigeration based system cannot fit.	
2 Valve towers and countertop models		Typically used in full service, bottle service and craft beverage applications	
3 Valve towers and Push Button (PB) models		Typically used in Self Service applications	

Towers

CBR-V1WHT
CBR-V1C

CBR-V1C-MINI

CBR-V2WHT
CBR-V2C

CBR-V2GLD

CBR-V2C-MINI

CBR-V3WHT
CBR-V3C



Model	Finish	Description	Size	Shipping Weight
CBR-V1WHT	White	Single Valve, Single Product Sparkling or Still	20" Height 12.25" Bottle Clearance	11 lbs
CBR-V1C	Chrome	Single Valve, Single Product Sparkling or Still	20" Height 12.25" Bottle Clearance	11 lbs
CBR-V1C-MINI	Chrome	Single Valve, Single Product Short Height Cobra Tower Sparkling or Still	13.57" Height 5.83" Bottle Clearance	8 lbs
CBR-V2WHT	White	Two Valve, Two Product Sparkling & Still Water	20.25" Height 12.5" Bottle Clearance	14 lbs
CBR-V2C	Chrome	Two Valve, Two Product Sparkling & Still Water	20.25" Height 12.5" Bottle Clearance	14 lbs
CBR-V2GLD	Gold	Two Valve, Two Product Sparkling & Still Water	20.25" Height 12.5" Bottle Clearance	14 lbs
CBR-V2C-MINI	Chrome	Two Valve, Two Product Short Height Cobra Tower, SSQ Sparkling & Still Water	15.44" Height 7.7" Bottle Clearance	12 lbs
CBR-V3WHT	White	Three Valve, Three Product Combination of Sparkling & Still Water	20.5" Height 12.74" Bottle Clearance	15 lbs
CBR-V3C	Chrome	Three Valve, Three Product Combination of Sparkling & Still Water	20.5" Height 12.74" Bottle Clearance	15 lbs

Towers

LIT-V2C



LIT-V3C



CRVS-V2C



CR-X3PB-COMP



Model	Finish	Description	Size	Shipping Weight
LIT-V2C	Chrome	Two Valve, Two Product LED Illuminated Product Medallions Sparkling & Still Water	20" Height 12.73" Bottle Clearance	14 lbs
LIT-V3C	Chrome	Three Valve, Three Product LED Illuminated Product Medallions Combination of Sparkling & Still Water	21.79" Height 12.73" Bottle Clearance	15 lbs
CRVS-V2C	Chrome	Two Valve, Two Product Sparkling & Still Water	19.5" High Tower 12.25" Bottle Clearance	13 lbs
CR-X3PB-COMP	Chrome	3 Button single spout faucet For use with the CP2000-R-UC-BH Low volume applications only	12.5" Height 9" Bottle Clearance	

Towers

CM-V2W



CM-2PB-SB



CM-2PB



CM-1PB



Model	Finish	Description	Size	Shipping Weight
CM-V2W	Chrome	Counter Mount or Wall Mount Dispenser Two Pull Handle Faucets Sparkling & Still	10.69"W x 10"D x 20.75"H 12" Bottle Clearance	10 lbs
CM-2-PB-SB	Chrome	Counter Mount Dispenser, Two LED Push button valves Sparkling & Still	12"W x 15.13"D x 17"H 12" Bottle Clearance	12 lbs
CM-2-PB	Chrome	Counter Mount Dispenser, Two LED Push button valves Sparkling & Still	10.25"W x 8.75"D x 18.5"H 12" Bottle Clearance	11 lbs
CM-2-PB-RDP	Chrome	Counter Mount Dispenser, Two LED Push button valves Integrated Recessed Drain Pan Sparkling & Still	10.625"W x 10"D x 18.5"H 12" Bottle Clearance	12 lbs
CM-1PB	Water Graphics	Push Button Counter Mount Dispenser AquaZone Graphics, built in drain Sparkling or Still	4.5"W x 9"D x 17.875"H 10" Bottle Clearance	10 lbs

Drip/Drain Pans

DP-CT
DP-CT-L/D



RDP-1SSQ-1CL



RDP-1SSQ-2CL



RDP-3-SSQ



Model	Description	Size	Shipping Weight
DP-CT	Stainless countertop mount drain pan, 1/2" drain pipe	10"W x 6"D x 0.75"H	2 lbs
DP-CT-LD	Stainless countertop mount drip pan, no drain	10"W x 6"D x 0.75"H	2 lbs
RDP-1SSQ-1CL	Flush mount, stainless drain pan and tower mount. Crysalli Logo stamped for use with CBR-V1	12"W x 15.125"D x 0.75" Recessed	4 lbs
RDP-1SSQ-2CL	Flush mount, stainless drain pan and tower mount. Crysalli Logo stamped for use with CBR-V2	12"W x 15.125"D x 0.75" Recessed	4 lbs
RDP-3-SSQ	Flush mount, stainless drain pan and tower mount. For use with CBR-V3, LIT-V3C, CRVS-V2C	15"W x 18.125"D x 0.75" Recessed	5 lbs

Remote Chillers

CR-UCM1



CR-UCW-BH



CR-UCM2
CR-UCM2-SW-2
CR-UCM2-2CL



CR-UCM2-S0096
CR-UCM2-2CL-S0096



Model	Description	Size	Shipping Weight
CR-UCM1	Remote Chiller unit Sparkling & Still 50 ltr/13 gal per hr @<40° Up to 35ft max trunk line run	12"W x 23.5"D x 24.5"H	115 lbs
CR-UCM2	Remote Chiller unit One or Two Coil (2CL) versions Sparkling & Still 80 ltr/21 gal per hr @<40° Up to 45ft max trunk line run	20"W x 20"D x 20"H	165 lbs
CR-UCM2-2CL	Remote Chiller unit One or Two Coil (2CL) versions Sparkling & Still 80 ltr/21 gal per hr @<40° Up to 45ft max trunk line run	20"W x 20"D x 20"H	165 lbs
CR-UCM2-S0096	Remote Chiller unit High cap. ext. pump Sparkling & Still 80 ltr/21 gal per hr @<40° Up to 75' trunk line run	20"W x 26"D x 20"H	185 lbs
CR-UCM2-2CL-S0096	Remote Chiller unit High cap. ext. pump Sparkling & Still 80 ltr/21 gal per hr @<40° Up to 75' trunk line run	20"W x 26"D x 20"H	185 lbs
CR-UCW-BH	Remote Chiller unit Still Water Only 37 ltr/10 gal per hr @<40° Up to 35ft max trunk line run	12"W x 18.75"D x 24.5"H	85 lbs
CR-UCM2-SW-2	Remote Chiller Two Coil unit Still Water Only 68 ltr/18 gal per hr @<40° For two valve or multi tower applications Up to 45ft max trunk line run	20"W x 20"D x 20"H	135 lbs

—RO: Internal upgrade of chiller for use with Reverse Osmosis Water, Wine or Coffee applications.
Add —RO to the end of the model number.

Countertops

CR-1
CR-1SW



CR-1-3V



CR-1-PB
CR-1SW-PB



CR-1PB-3V



Model	Description	Size	Shipping Weight
CR-1	Countertop 1 Series Sparkling & Still 9.5 lbs ice bank 50 ltr/13 gal per hr @ <40°	12.5"W x 31.38"D x 24.5"H 12" Bottle Clearance (Drip Tray 6"D included)	115 lbs
CR-1-3V	Countertop 1 Series Sparkling, Still & Ambient Three Valve Pull Handle Faucets	12.5"W x 31.38"D x 24.5"H 12" Bottle Clearance (Drip Tray 6"D included)	115 lbs
CR-1-PB	Countertop 1 Series Sparkling & Still Push Button Dispensing Valves	12.5"W x 29.38"D x 24.5"H 12" Bottle Clearance (Drip Tray 6"D included)	115 lbs
CR-1PB-3V	Countertop 1 Series Sparkling & Still & Ambient Three Valve Push Button Dispensing Valves	12.5"W x 23.75"D x 24.5"H 12" Bottle Clearance (Drip Tray 6"D included)	115 lbs
CR-1SW	Countertop 1 Series Still Water Only Two valve 37 ltr/10 gal per hr @ 40°	12.5"W x 25.75"D x 24.5"H 12" Bottle Clearance (Drip Tray 6"D included)	65 lbs
CR-1SW-PB	Countertop 1 Series Still Water Only Two Push Button Dispensing Valves 37 ltr/10 gal per hr @ 40°	12.5"W x 23.75"D x 24.5"H 12" Bottle Clearance (Drip Tray 6"D included)	65 lbs

Countertops

CR-2
CR-2SW



CR-2-3V



CR-2-PB
CR-2SW-PB



CR-2PB-3V



Model	Description	Size	Shipping Weight
CR-2	Countertop 2 Series Sparkling & Still Pull Handle Faucets 25 lbs ice bank 80 ltr/21 gal per hr @ <40°	20"W x 28"D x 24.75"H 12" Bottle Clearance (Drip Tray 6"D included)	165 lbs
CR-2-3V	Countertop 2 Series Sparkling, Still, & Ambient Three Valve Pull Handle Faucets	20"W x 28"D x 24.75"H 12" Bottle Clearance (Drip Tray 6"D included)	165 lbs
CR-2-PB	Countertop 2 Series Sparkling & Still Push Button Dispensing Valve	20"W x 26"D x 24.75"H 11" Bottle Clearance (Drip Tray 6"D included)	165 lbs
CR-2PB-3V	Countertop 2 Series Sparkling & Still & Ambient Three Valve Push Button Dispensing Valves	20"W x 28"D x 24.75"H 12" Bottle Clearance (Drip Tray 6"D included)	165 lbs
CR-2SW	Countertop 2 Series Still Water Only Two valve 68 ltr/18 gal per hr @ 40°	20"W x 28"D x 24.75"H 12" Bottle Clearance (Drip Tray 6"D included)	135 lbs
CR-2SW-PB	Countertop 2 Series Still Water Only Two Push Button Dispensing Valves 68 ltr/18 gal per hr @ 40°	20"W x 28"D x 24.75"H 12" Bottle Clearance (Drip Tray 6"D included)	135 lbs

For Self Service application, add **-HEX** to the end of model number. **Not available for Push Button.**
-RO: Internal upgrade of chiller for use with Reverse Osmosis Water, Wine or Coffee applications.
 Add **-RO** to the end of the model number.

Cabinets

CR-CPS-DI
CR-CPSW-DI



CR-CPS-FS



CR-MCPS



CCP2000-UCR-CBR



Model	Description	Size	Shipping Weight
CR-CPS-DI	Drop-In Cabinet Ice Cooled Cold Plate System with CBR-V2 tower Still & Sparkling 40 lbs Ice Storage	17"W x 25"D x 50.75"H 12.5" Bottle Clearance	115 lbs
CR-CPS-FS	Free Standing Cabinet Ice Cooled Cold Plate System with CBR-V2 tower Still & Sparkling 40 lbs Ice Storage	17"W x 24"D x 62.75"H 12.5" Bottle Clearance	115 lbs
CR-MCPS	Self Contained Mobile Cabinet Ice Cooled Cold Plate, with integrated water filter, drain bucket, CO2 Regulator & tank mounting brace	31"W x 26"D x 63"H 12.5" Bottle Clearance	150 lbs
CR-CPSW-DI	Drop-in Cabinet Ice Cooled Cold Plate System with CBR-V2 tower Still Water Only 40 lbs ice storage	17.13"W x 24.9"D x 40"H 12.5" Bottle Clearance	90 lbs
CCP2000-UCR-CBR	CP2000-UCR, CBR-V2C and drain pan integrated into a SS cabinet with built in water filter and CO2 tank mount. Plug and play design. For Low Volume Applications	24"W x 22"D x 58.25"H 12.5" Bottle Clearance	200 lbs

Low Volume Units

CP2000-R-UC-BH
CP2000-SW-BH



CP2000-CT2



CP2000-CT3



CP2000-CT2-PB



CP2000-CT3-PB



CP2000 Series
capacity 50, 12oz
Cups per hour
under 40°

Model	Description	Size	Shipping Weight
CP2000-R-UC-BH	Remote Chiller unit, Sparkling & Still 6' recirculating trunkline length For exclusive use with CR-X3PB-COMP or draft towers found on pages 4 & 5	11.75"W x 17.5"D x 16.5"H	80 lbs
CP2000-SW-BH	Remote Chiller unit, Still Water only bulk head connection point, one product outlet 8' max trunkline	11.75"W x 17.5"D x 16.5"H	75 lbs
CP2000-CT2	Countertop Sparkling & Still Pull Handle Faucets	12"W x 26"D x 20.75"H	80 lbs
CP2000-CT3	Counter mount Sparkling, Still, & Ambient Pull Handle Faucets	12"W x 26"D x 20.75"H	80 lbs
CP2000-CT2-PB	Countertop Sparkling & Still Push Button Dispensing	12"W x 21.5"D x 20.75"H	80 lbs
CP2000-CT3-PB	Counter mount Sparkling & Still Push Button Dispensing	12"W x 21.5"D x 20.75"H	80 lbs

Low Volume Units



Model	Description	Size	Shipping Weight
Serenity-X3	Undercounter Artisan water system kit with CR-X3PB faucet, 10.5"W x 14.375"D x 18.125"H CR-12FC filter system install kit and leak detector device.	(Complete Package)	60 lbs
Serenity-CBRM	Undercounter Artisan water system kit with CBR Mini tower, 10.5"W x 14.375"D x 18.125"H CR-12FC filter system install kit and leak detector device.	(Complete Package)	60 lbs
CP-JR-UC-SW-BH	JR Undercounter Still water only chiller One product outlet. Low volume.	10.5"W x 10.5"D x 18.125"H	
CP-JR-CT2FR	JR Model Sparkling & Still Pull Handle faucets and integrated 2FC Filter and water pressure reducer valve	10.75"W x 18.12"D x 14.87"H	60 lbs
CP-JR-CT2FR-PB	JR Model Sparkling & Still LED Push Button valves and integrated 2FC filter and water pressure reducer valve	10.75"W x 18.125"D x 17"H	60 lbs
CP-JR-CT1SWF	JR Model Still Water only , 1 Pull Handle faucet and integrated 2FC filter system	10.625"W x 21.25"D x 17"H	60 lbs
CP-JR-CT1SWF-PB	JR Model Still Water only , 1 LED Push Button valve and integrated 2FC filter system	10.75"W x 18.12"D x 14.87"H	60 lbs

–RO: Internal upgrade of chiller for use with Reverse Osmosis Water, Wine or Coffee applications.
Add –RO to the end of the model number.

Install Kits

	Model	Description	Shipping Weight
	CR-KIT-CT	Installation Kit for Countertop units, CR-1 & CR-2, Includes: Fittings and oetiker clamps and extra tubing to install the filter systems and Countertop unit	6 lbs
	CR-KIT-UCM	Installation Kit for Remote Chiller Units, UCM1 & UCM2, Includes: 5ft of CR-4L38 trunkline, various fittings and oetiker clamps, extra tubing and insulation to install the filter system, CR-UCM# and CBR or CM tower	7 lbs
	CR-KIT-SWCT	Install Kit for Countertop Still water chillers, CR-1SW and CR-2SW, Includes: Various fittings and oetiker clamps, and extra tubing. Still Water Units Only	6 lbs
	CR-KIT-SWUC	Install Kits for Remote Still water chillers, CR-UCW, CR-UCM2-SW2 & and CP2000-SW-BH, Includes: 5' of CR-4L38 Trunkline, various fittings and oetiker clamps, adapters, and extra tubing. Still Water Units Only	6 lbs
	CR-KIT-CPS	Install kit for CR-CPS model series, includes: Water filter fittings, angle stop adaptor and 8' 3/8 hose	6 lbs
	CR-KIT-CPCT	Kit includes fittings needed to complete the installation of CR-14FC filter system to Countertop CP2000-CT2. Includes: Water pressure reducer valve, fittings, and extra tubing. CP2000 CT Series Only	6 lbs
	CR-KIT-CPUC	Kit includes fittings needed to complete the installation of CR-14FC filter system to Remote Chiller CP2000-R-UC-BH and Tower or Faucet. Includes: Water pressure reducer valve, fittings, 6' of CR-4L38 tubing, and extra tubing. CP2000 UC Series Only	6 lbs
	CBR2-FKM-V2	Fitting Kit for adding a 2nd CBR-V2C or other 2 valve dispenser tower off the trunkline from a UCM remote chiller.	6 lbs
	CBR2-FKM-V3	Fitting Kit for adding a 2nd CBR-V3C or other 3 valve dispenser tower off the trunkline from a UCM remote chiller.	6 lbs
	CR-4L38	Four line (3/8") insulated 2" Diameter trunk line Two product lines, two re-circulating lines 5 ft is included in the UCM install kit For UCM Models	1 lb per ft
	CR-3741	Primary High Pressure CO2 Regulator for CO2 Tank	3 lbs
	CR-T5261SN	Secondary High Pressure CO2 Regulator for split CO2 system	2 lbs

Water Filters

	Model	Description	Shipping Weight
	CR-24FC	Twin Filter System with Compact Fibredyne filters, 3/4" inlet & outlet. 19" High X 17" Wide 5 gpm, 30,000 gal, TOC & 1/2 micron filtration	11 lbs
	CR-24FCP	Twin System with Pre Filter and Fibredyne filters, 3/4" inlet & outlet. 19" High x 22" Wide 5 gpm, 30,000 gal, TOC & 1/2 micron filtration	11 lbs
	CR-14FC	Single Filter System with Compact Fibredyne filters, 3/4" inlet & outlet. 15" High X 8" Wide 2.5 gpm, 15,000 gal, TOC & 1/2 micron filtration For the CP2000 Low Volume Series Only	11 lbs
	CR-14FCP	Single System with Pre Filter and Fibredyne filters, 3/4" inlet & outlet. 15" High x 14" Wide 2.5 gpm, 15,000 gal, TOC & 1/2 micron filtration For the CP2000 Low Volume Series Only	11 lbs
	4FC	Replacement Water Filter High Capacity 15,000 gallon Fibredyne Cartridge	1 lbs
	4FC-L	Replacement Water Filter Lead Reduction	1 lbs
	ECP5-10	Replacement Water Filter Pleated Pre-Filter	1 lbs
	2FC	Replacement Water Filter 6,000 gallon capacity Compact Fibredyne cartridge For the CP-JR models only	1 lbs

Additional and custom configured Water Filtration Systems for individual water quality needs are available
The use of Non Crysalli Approved water filter systems can result in undesirable water quality and product performance

Chiller Accessories and Upgrades

	Model	Description	Shipping Weight
	CR-ABUCM	Air Baffle Accessory kit for Undercounter models; CR-UCM1 & CR-UCM2. For Undercabinet mount applications	
	CR-TFB1	Thermostatic Fan Box Additional air circulation in cabinets, for use with Remote Undercounter Chillers	
	CR-WMB1	Wall Mounting bracket for the CR-UCM1	25 lbs
	CR-WMB2	Wall Mounting bracket for the CR-UCM2	25 lbs
	-RO	Stainless steel pump upgrade to Chiller for use with Reverse Osmosis water, Coffee or Wine applications. Add -RO to the end of the model number	
	CR-804-001	Low volume water boost system	
	CR-804-023	Water boost system	
	CR-804-026	Water boost system	
	S0747-SET	4.25" Leg Kit. (standard on the CR-UCM1, CR-1, CR-2 series models).	
	S1318-SET	Adjustable Cushion feet (standard on the CR-UCM2)	
	CR-BG2B-FF	Bar Gun Two Button Sparkling and Still Fast Flow 30" hose	
	CR-WBM-4004	Flavor & Water Bar Gun Six Button (four syrup, one rinse, one sparkling water) regular flow	
	CR-WBM-604	Flavor Shot Bar Gun 5 Button (four flavor syrup, one rinse) regular flow	
	CR-4V-BIB-Kit	Flavor Shot BIB Kit for four flavor Bar Gun Includes; BR2B 2x2 rack, pumps, regulators, tubing and bag connectors. For use with WBM bar guns to dispense BIB flavor additives	125 lbs
	CR-LBS10JG	For use with any Crysalli chiller system Leak Block Sensor. In-line Leak Detector with Auto Shut-Off.	
	PASVPP6	Angle Stop Adapter Splice	
	CR-BPFK	Crysalli Water Filter system Bypass fitting kit	
	CR-IL-COMP	External inline flow control compensator	

Draft Tower Accessories and Upgrades

	Model	Description	Shipping Weight
	X100306C	Ergo Chrome Top Handle Sparkling Water graphics	
	X100306C	Ergo Chrome Top Handle Chilled Still Water graphics	
	X100306C	Ergo Chrome Top Handle Still Water graphics	
	X100302B	Ergo Black Top Handle Sparkling Water graphics	
	X100302B	Ergo Black Top Handle Chilled Still Water graphics	
	X100302B	Ergo Black Top Handle Still Water graphics	
	CR-100301-C	Chrome Ergonomic Style Tap Handle 4" Tall. No branding Use with CR-SSQ1231 Faucets	
	CR-12K02201	Chrome Plated Brass Handle 2.5" tall	
	CR-MDLN-V1	For CBR-V1, One Straight Medallion Holder Specify Water type	
	CR-MDLN-V2	For CBR-V2, Two Straight Medallion Holders Sparkling and Chilled Still	
	CR-MDLN-V3	For CBR-V3, Three Straight Medallion Holders Sparkling, Chilled Still and Still Ambient	



Mission:

- Crysalli strives for excellence as leaders, educators, innovators and producers of water and other high quality beverage dispensing equipment.

Vision:

- Maintain a pure and simple focused approach to our equipment and customer experiences.
- Proactive empowerment, innovation and ownership of customer solutions.
- Pay attention to the details.
- Treat everyone as we desire to be treated.
- Never let profits get in the way of doing the right thing.
- Build and maintain enduring relationships.
- Continual education and personal improvements.
- Take the time to enjoy a cold glass of sparkling water.
- Have fun and enjoy selling and supporting Crysalli.

Product Styles

Commercial Remote Chillers

- Sparkling and Still
- Still Chilled only
- Used with Draft Tower options

Commercial Countertop Chillers

- Sparkling and Still
- 2 and 3 valve configurations
- Still Chilled only

Low Volume CP Series

- Undercounter Chillers
- Countertop Chillers

Always include an Install Kit with new installation systems

Always include water filtration system with new installations

- Contact your local Distributor for replacement water filter cartridges

Warranty

- Commercial Warranty: 1 year Parts and Labor
 - Remote UCM units must be used with Crysalli Dispensing towers to be eligible for warranty coverage
- All Residential Units: 1 year Parts 90 days Labor

Prices

- Prices are FOB Hayward, California
- All Prices and specifications are subject to change without notice
- Product found in Auto Quotes
- Contact factory for Minimized Advertising Pricing (MAP) policy

Resources

- Available in AutoQuotes
- CAD files
- 3D CAD files
- REVIT files



Why Crysalli?

- Made in the USA
- 1 Year Parts and Labor Warranty
- All units 120 volts
- NSF/ETL and UL Approved
- City of LA Approved
- Detailed Installation and Fitting Kits
- CO2 Regulators and other accessories
- Comprehensive install instructions
- Multiple dispensing tower selections
- Custom built models and configurations available
- Local availability and support via a nationwide network of distribution companies
- Serviced by a nationwide network of installers and service companies

Crysalli Artisan Water
1739 Sabre Street
Hayward, CA 94545
www.crysalli.com
510.732.0100

